

Amarri

®





The Model 2720, 2700, and the 1350 are Amarr's top-of-the-line high R-Value Doors. Constructed using 2" or 1 3/8" foamed-in-place polyurethane insulation which creates a strong monolithic panel that is energy efficient. The Model 2720 has a 20-gauge steel front skin that provides a perfect option for heavy industrial applications.

Each model is secured with standard 14-gauge, galvanized steel hinges. The interior skin of each section has two continuous horizontal 20-gauge reinforcing strips. The section joint is thermally broken and chemically bonded with a pressure-sensitive adhesive sealant. An EPDM rubber weather seal further enhances the performance of the joint.

OPTIONAL PASS DOOR



Available for Model 2700 only in door sizes up to 16'2" wide x 16' tall. Wind Load option not available.

WARRANTIES

- 10-year Limited Warranty on the paint and finish
- 1-year Limited Warranty on hardware
- See your dealer or visit amarr.com for complete warranty details

Construction

Model 2720

Extra Heavy-duty 2" 20 Gauge Foamed-in-Place Door

MODEL 2720
R-Value
19.40*

Model 2700

Heavy-duty 2" Foamed-in-Place Door


MODEL 2700
R-Value
19.40*

Model 1350

Heavy-duty 1-3/8" Foamed-in-Place Door

MODEL 1350
R-Value
14.46**

*Based upon independent laboratory test results.
**Calculated door section R-value is in accordance with DASMA TDS-163.



TRIPLE-LAYER Steel + Insulation + Steel

Track: All Amarr Doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow-the-Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit our website at www.amarr.com.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

PANEL



RIBBED PANEL WITH STUCCO EMBOSSMENT
2720 is Flush Panel with stucco embossment.



OPTIONAL FULL-VIEW PANEL
Clear and Dark Bronze Anodized Aluminum, White Powder Coat, or Custom Powder Coat colors. Not available for 1350.

WINDOW OPTIONS



26" x 13" DOUBLE INSULATED
ACRYLIC WINDOWS WITH BLACK FRAME



24" x 6" DOUBLE INSULATED
ACRYLIC WINDOWS WITH BLACK FRAME



24" X 12" INSULATED GLASS

COLORS

Actual paint colors may vary from samples shown.



WHITE



COMMERCIAL
BROWN
(Model 2700 only)

The Model 2700 and 1350 use a brighter tone of white color than the 2720.

Amarr steel doors arrive pre-painted; for custom colors, exterior latex paint must be used. Visit amarr.com for instructions on painting.



165 Carriage Court
Winston-Salem, NC 27105

800.503.DOOR
www.amarr.com



FOR PRODUCT BINDER:
1.800.503.3667

FOR TECHNICAL QUESTIONS:
1.877.512.6277

Amarr reserves the right to change specifications and designs without notice and without incurring obligations.

Amarr Company's products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents.

Amarr is a registered trademark of Amarr Company, North Carolina, U.S.A.

©2013 Amarr Garage Doors
Printed in USA Form #6210513/10M/HA